


# ATACAMA UNIT - HP is designed mainly for use in combination with HEAT PUMPS

Units ATACAMA HP are equipped by 3 or 4 rows coils with special lamela distances for increasing heating or cooling output. In summer you can use it as a very effective cooling device and in winter as a very cost saving heating solution. Both is the best to use in combination with heat pumps.

## Technical parameters unit ATACAMA-HP


### Heat exchanger parameters:

Max. operating water temperature 120°C  
 Max. operating pressure 1.6Mpa  
 Connecting dimensions of all heat exchangers - external thread G 3/4".  
 Condensation pan and mounting bracket are included.



		ATACAMA-HP-4	
		EC	
Fan type	-	EC	
Operating area (ceiling heigh 4m)	m2	0-1000	
Air flow	m3/h	4400	4000
Heating output (45°C/35°C)15°C	kW	20,1	24,2
Cooling output range (7°C/12°C/30°C)	kW	18,1	22,1
Number of exchanger rows	-	3	4
Working information of exchanger	maximum working temperature of water is 120°C; maximum working pressure 1,6Mpa; exchanger connection G 3/4"		
Maximal horizontal range *	m	12	10
Maximal vertical range *	m	6	5
Noise level **		51,6	51,9
Unit weight with bracket***	kg	25 / 28	31 / 35
Capacity of water in exchanger	dm3	3	4
Power supply	V/Hz	1 ~ 230/50-60	
Motor output	W	379	390
Motor current	A	1,63	1,7

\* Maximum distance of airstream - speed of air is 0,5m/s  
 \*\* Acoustic pressure in 5m, Q=2  
 \*\*\* weight of unit without water



# Air Heating and cooling unit for heat pumps

www.xvent.cz

